

CLEVERTRONICS LP LED WEATHERPROOF SUPALITE



PRODUCT INFORMATION

| | |
|-----------------------|--|
| Part Number | CWFLED-DALI |
| MIC | AUE02220010002 |
| Description | LP Premium LED Weatherproof Supalite flood unit, surface mounted Emergency Light |
| Construction | Polycarbonate |
| Mounting | Surface wall mount (hard wired supply connection) |
| Dimensions L x W x H | Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm |
| Weight | 3.6kg |
| Operating Mode | Non-maintained |
| Testing System | DALI Registered |
| Battery | Lithium Iron Phosphate, 6.4V 3200mAh |
| Charging Method | Intelligent current limited constant voltage |
| Lamp(s) | 2 x LED Heads (adjustable), 600lm per lamp head |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.0 Watts (Standby), 5.4 Watts (Max) |
| IP Rating | IP65 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =N/A C ₉₀ =N/A |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|------------------------|--|
| 1550290 | BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt |
| CCPLED-WP-18V625C-CKIT | LED Power Pack, 18V 625mA, IP Loom,CT,LP |
| 1100550 | WP Led Head, c/w Led's & Loom |
| 8003065 | PCA: DALI Node #CT10629-Ax Horizontal |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order



Isolux plot and value table for a 30m x 30m area serviced by a Weatherproof Supalite with each LED lamp head tilted down 30°, rolled out 30°. The Weatherproof Supalite mounted on the wall at a height of 3m and 6m (values in lux).

