



## CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO SPOTLIGHT EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SPOT
Description	L10 Lifelight PRO, High Performance, Spotlight Style Emergency Light
Mounting	Lamp head assembly - Ceiling or wall mount with adjustable lamp head direction Control gear and battery – Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 105mm 100mm x 60mm (Lamp Head and Swivel)
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	Manual Test Switch
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4W (standby) 2.2W (max during 16 hour charge)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C <sub>0</sub> =D50 C <sub>90</sub> =D50

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	Lamps: 2 x 3W LED Round Head Assembly - White
1530230	Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket
LLIFE-PRO-CKIT	PCA: Lifelight Pro Control Gear

