




CLIFE-PRO-HV-SPOT-BLK

Lifelight Pro Single Spot Emergency, Recessed Mount, LP, Zoneworks XT Hive, 450lm, Black



PRODUCT INFORMATION

Part Number	CLIFE-PRO-HV-SPOT-BLK
MIC	AUT02810250001
Description	Lifelight Pro Single Spot Emergency, Recessed Mount, LP, Zoneworks XT Hive, 450lm, Black
Construction	Lamp head assembly with adjustable lamp head direction Control gear and battery – Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Mounting	Ceiling or wall mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 105mm x 100mm x 60mm (Lamp Head and Swivel)
Operating Mode	Non-Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 6.4Ah 20.5Wh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush Current (Max)	14.141A/76μS
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
1100817	LED Head Assembly
AUM02870070002 CLIFE-PRO-CKIT-HV	Driver Pack
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.