




LLIFEM-PRO-RECWP-WHT-UPS

Lifelight PRO, High Performance, IP65 recessed Emergency Light, UPS Controlled, White



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-RECWP-WHT-UPS
MIC	AUT01520060001
Description	Lifelight PRO, High Performance, IP65 recessed Emergency Light, White Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others)
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm head diameter
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Maintained - If a 220V/240V AC supply is applied to the luminaire the LED lamp Head will illuminate. To operate the fitting in Non-Maintained mode and External sensing relay (supplied by others) will be required to sense the loss of supply to the local lighting circuit and facilitate the changeover to the 220V/240V AC backup/UPS supply
Testing System	Manual Test Switch
Battery	n/a
Charging Method	n/a
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts
IP Rating	IP65 (Lamp head only)
IK Rating	IK10
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
AUM01570010001	EM Driver
LLIFEM-PRO-CKIT-UPS	
1100817	Led Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.