



LLIFE-PRO-HV-BLK

CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO
RECESSED EMERGENCY (ZONWORKS XT HIVE), Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HV-BLK
MIC	AUT01810100002
Description	L10 Optimum LifeLight PRO, high performance, recessed Emergency Light, Black
Construction	PC/ABS Head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (98mm with adaptor plate)
Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (MAX)
Inrush Current (Max)	13.313A @ 66µs
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01870010001 LLIFE-PRO-CKIT-HV	Driver Pack
1100871	LED Head
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.