




CLIFE-PRO

Lifelight Pro Emergency, Recessed Mount, CLP, Clevertest Plus



PRODUCT INFORMATION

Part Number	CLIFE-PRO
MIC	AUT02310010004
Description	Lifelight Pro Emergency, Recessed Mount, CLP, Clevertest Plus
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (98mm with adaptor plate)
Cut-Out	51mm (85mm with adaptor plate)
Minimum Depth	200mm (120mm with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Inrush Current (Max)	18.9A@138μS
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
AUM02370100003 CLIFE-PRO-CKIT	Driver Pack
1100868	LED Head Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.