



LLIFE-PRO

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Clevertest Plus



PRODUCT INFORMATION

Part Number	LLIFE-PRO
MIC	AUT01310010004
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Clevertest Plus
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (98mm with adaptor plate)
Ceiling Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Inrush Current (Max)	13.313A @ 66µs
Earth Leakage	0.326mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80, C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01370040001 LLIFE-PRO-CKIT	Driver Pack
1100868	LED Head

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.