



## LLIFE-PRO-DALI-BLK

CLEVERTRONICS L10 LIFELIGHT PRO  
RECESSED EMERGENCY - BLACK



### PRODUCT INFORMATION

Part Number	LLIFE-PRO-DALI-BLK
MIC	AUT01210260004
Description	L10 Optimum Lifelight PRO, Recessed Emergency Light, Black
Construction	PC/ABS head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (98mm with adaptor plate)
Ceiling hole cut-out	51mm (85mm with adaptor plate)
Minimum ceiling depth	200mm (120mm with adaptor plate)
Weight	0.85kg
Operating Mode	Non-Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max during 16-hour charge)
Inrush Current (Max)	13.313A @ 66µs
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1° to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100871	LED Head
AUM01270200002 LLIFE-PRO-CKIT-DALI	Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order