




## LLIFEM-PRO-SA-HV

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained, Switched Active, Zoneworks XT Hive



### PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SA-HV
MIC	AUT01810170001
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained, Switched Active, Zoneworks XT Hive
Construction	PC/ABS Head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (98mm with adaptor plate)
Cut-Out	51mm (85mm with adaptor plate)
Weight	0.8kg
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby) 5 Watts (Max)
Inrush Current (Max)	12.093A @ 87.3μS
Earth Leakage	0.361mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80, C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100868	LED Head
AUM01870320001 LLIFEM-PRO-SA-CKIT-HV	Driver Pack
8003191	HV Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.