



LLIFEM-PRO-SM-SA-HV

CLEVERTRONICS L10 MAINTAINED LIFELIGHT PRO SURFACE MOUNT
EMERGENCY (ZONWORKS XT HIVE)



PRODUCT INFORMATION

| | |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Part Number | LLIFEM-PRO-SM-SA-HV |
| MIC | AUT01810180001 |
| Description | L10 Lithium Nanophosphate LifeLight PRO, high performance Surface Mounted Emergency Light, Maintained (switched active on/off control of LED's) |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Ceiling Cut-Out | N/A |
| Minimum Ceiling Depth | N/A |
| Weight | 0.7kg |
| Operating Mode | Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm) |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.7 Watts (Standby) 5 Watts (Max) |
| Inrush Current (Max) | 12.093A |
| Earth Leakage | N/A |
| IP Rating | IP20 |
| IK Rating | N/A |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=D80, C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530231 | Battery |
| 8003081 | LED Head |
| 8003501 | EM Driver |
| 8003191 | HV Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.