



## LLIFEM-PRO-SM-HV

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive



### PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SM-HV
MIC	AUT01810260001
Description	Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Maintained
Testing System	Zoneworks XT Hive (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby) 3.0W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003081	Emergency LED Head Assembly
8003501	Driver
8003191	Emergency Node – HIVE (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.