



## LLIFEM-PRO-SM-SA-BLK

L10 Lifelight Pro Emergency Luminaire  
Surface Mount, Switched Active, Black



### PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SM-SA-BLK
MIC	AUT01310480001
Description	L10 Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Switched Active, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	4.7W (Lamp ON Max), 2.4W (Lamp ON Standby), 0.7W (Lamp OFF Standby)
Inrush Current (Max)	12.093mA
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003081	LED Head Assembly
8003501	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.