



LLIFE-PRO-SMS-HV-SPOT

Lifelight Pro Single Spot Emergency, Surface Mount, L10
Nanophosphate, Zoneworks XT Hive, 450lm



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SMS-HV-SPOT
MIC	AUT01810280001
Description	Lifelight Pro Single Spot Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, 450lm
Construction	PC/ABS Head, Metal Enclosure. Double/reinforced insulation between supply and battery circuit of lamp control gear, with external RF antenna
Mounting	Surface Mounted
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (lamp head and swivel assembly)
Weight	2.0kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
Inrush Current (Max)	13.313A @ 66µs
IP Rating	IP20
Operating Temperature	1°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01870940001 LLIFE-PRO-SMS-CKIT-HVEXTA-NP	Lifelight Pro, Control Only, HVEXTA, L10
8003191	LED Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order