



LLIFEM-PRO-SM-UPS

CLEVERTRONICS LIFELIGHT PRO IP65 WEATHERPROOF
SURFACE MOUNT EMERGENCY – MAINTAINED – UPS OPERATED



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SM-UPS
MIC	Preliminary Datasheet
Description	Optimum Maintained Lifelight PRO, High Performance, Surface Mounted Emergency Light. Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others)
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	If a 240V AC/DC supply is applied to the luminaire the LED lamp head will illuminate. To operate the fitting in Non-Maintained mode an external sensing relay (supplied by others) will be required to sense the loss of supply to the local lighting circuit and facilitate the changeover to the 240V AC/DC backup/UPS supply
Testing System	N/A
Battery	N/A
Charging Method	N/A
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.4W
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8050170	LED: HWSUB: CT10668-D1

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order