




LLIFE-PRO-SMS-SPOT

Lifelight Pro Single Spot Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SMS-SPOT
MIC	AUT01310390001
Description	Lifelight Pro Single Spot Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus
Construction	PC/ABS Head, Metal Enclosure. Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Surface Mounted
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (lamp head and swivel assembly)
Weight	2.0kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.7W (Max)
Inrush Current (Max)	12.093A @ 87.3µs
Earth Leakage	0.364mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01370190001 LLIFE-PRO-SMS-CKIT-NP	Driver Pack
1100866	LED Head

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order