



LLIFE-PRO-SM

CLEVERTRONICS L10 LIFELIGHT PRO EMERGENCY LUMINAIRE
SURFACE MOUNT



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SM
MIC	AUT01310080001
Description	L10 Optimum Lifelight PRO, High Performance, Surface Mounted Emergency Light, Enabled with Clevertest Plus
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby) 2.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530231	BATT:L10 3.3V 5AH. 200mm lead, no BRKT
8003081	LED: PCA: LLPRO HEAD Alum #CT10640-D4 - GW CSHPM 'LT'
8002924	DRIVER: PCA: xLIFEPro SM #CT10142-L9 2C250/550 CTP AU

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.