

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT EMERGENCY (DALI)



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SM-DALI
MIC	AUT02210330002
Description	LP Premium Lifelight PRO, High Performance, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (standby) 2.7W (max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order