



CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT EMERGENCY SPOTLIGHT



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SMS-SPOT
Description	LP Lifelight PRO, High Performance, Surface Mount Emergency Spotlight
Mounting	Surface Mount, Ceiling or Wall with swivel and rotation of head
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (Lamp head and swivel assembly)
Ceiling hole cut-out	NA
Operating Mode	Non-Maintained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V
Power Consumption	0.4 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C (Ambient)
AS2293 Classification	N/A

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	2 x 3W LED Round Head Assembly – White
1550230	Battery, LP 3.2V 6400mAh.200mm lead.Brkt.
8002390	Driver, PCA:Lifelight Pro, Zoneworks Compatible
8001450	Network, Zoneworks Powerline Node

