



CLIFE-PRO-SMS-SPOT

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT EMERGENCY SPOTLIGHT



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SMS-SPOT
MIC	AUT02310120001
Description	LP Premium Lifelight PRO, High Performance, Surface Mount Emergency Spotlight Enabled with Clevertest Plus
Construction	PC/ABS Head, Metal Enclosure. Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Surface Mounted
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (lamp head and swivel assembly)
Weight	2.0kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead. BRKT
CLIFE-PRO-SMS-CKIT-NP	Lifelight Pro,Control Only, LP, NP

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order