



LLIFEM-PRO-SM

CLEVERTRONICS L10 LIFELIGHT PRO EMERGENCY LUMINAIRE
SURFACE MOUNT



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | LLIFEM-PRO-SM |
| MIC | AUT01310220001 |
| Description | L10 Optimum Lifelight PRO, High Performance, Surface Mounted Emergency Light, Enabled with Clevertest Plus |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.4W (Standby) 4.7W (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=D80 C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-----------------------------|
| 1530231 | Battery |
| 8003081 | Emergency LED Head Assembly |
| 8002924 | Driver |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.