



LLIFE-SM-DALI-BLK

CLEVERTRONICS L10 LIFELIGHT SURFACE MOUNT EMERGENCY, BLACK, DALI



PRODUCT INFORMATION

Part Number	LLIFE-SM-DALI-BLK
MIC	AUD01210080002
Description	L10 Optimum Lifelight, High Performance, Surface Mounted Emergency Light, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.6kg
Operating Mode	Non-Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.3 W (Standby), 3.0 W (Max)
Inrush Current (Max)	17.5A
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	Battery
8050176	Emergency LED Panel
8002939	Emergency Driver
8003060	Emergency Node – DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.