



CLIFE-SM-DALI-BLK

CLEVERTRONICS LP LIFELIGHT SURFACE MOUNT EMERGENCY BLACK



PRODUCT INFORMATION

Part Number	CLIFE-SM-DALI-BLK
MIC	AUD02210220002
Description	LP Premium Lifelight, High Performance, Surface Mounted Emergency Light, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High Intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3W (Standby), 4.5W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8050176	HWSUB: CT10696-D1
8002941	PCA: CLIFE CT10260-L5 1C650 HV Vert Connectors
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.