

CLEVERTRONICS L10 LIFELIGHT SURFACE MOUNT EMERGENCY, BLACK



PRODUCT INFORMATION

Catalogue Number	LLIFE-SM-BLK
MIC	AUD01310070001
Description	L10 Optimum Lifelight, High Performance, Surface Mounted Emergency Light, Enabled with Clevertest Plus, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	BATTERY:L10 3.3V 2.5AH 200mm ld, no Brkt
8002938	PCA: LLIFE CT10260-L5 1C550 CTP AU Vert Connectors

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order