

CLEVERTRONICS ECONOMY LIFELIGHT SURFACE MOUNT



PRODUCT INFORMATION

Catalogue Number	ELIFE-X-LI-SM
MIC	AUD03310010001
Description	Economy Lithium Lifelight, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 W (Standby), 1.3W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560160	BATT:EcoLith 3.2V 3.0Ah 170mm lead,NoBKT
8002986	PCA: ELIFE-X-SMS-LI CT10614-L2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order