



LUBPRO-TH-R

CLEVERTRONICS L10 ULTRABLADE PRO THEATER MASK



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | LUBPRO-TH-R |
| MIC | AUA01360400002 |
| Description | L10 Ultrablade Pro Recessed Blade Exit with Theatre Mask, Enabled with Clevertest Plus |
| Construction | PC/ABS body with PC diffuser |
| Mounting | Recessed Ceiling |
| Dimensions L x W x H | 317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate) |
| Cut-Out | 350mm x 48mm |
| Minimum Depth | 80mm |
| Weight | 1.1kg |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Nanophosphate 3.3V 2.5Ah |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | Theatre Mask, Running Man, Single Sided |
| Lamp(s) | 12 x Duris E3 LED, 100,000 hours |
| Inrush Current | 13.08A |
| Earth Leakage | 0.331mA |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.5 Watts (Standby), 3.9 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =N/A C ₉₀ =N/A |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------------------------|-------------|
| 1530050 | Battery |
| 8002178 | LED Strip |
| AUM01370010002 LUBPRO-CKIT | Driver Pack |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.