



LUBPRO-DALI-V-BLK

CLEVERTRONICS L10 ULTRABLADE PRO, BLACK



PRODUCT INFORMATION	
Part Number	LUBPRO-DALI-V-BLK
MIC	AUA01211360002
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit, Black
Construction	ABS frame with acrylic & PC diffuser
Mounting	Recessed Wall Mount
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
AS2293 Classification	C0=E1, C90=B1
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	Battery
8002178	LED Strip
AUM01270340003 LUBPRO-CKIT-DALI	Emergency Driver
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order