



## LUBPRO-UPS

L10 Lithium Nanophosphate Ultrablade Pro Blade Exit, supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply



### PRODUCT INFORMATION

Part Number	LUBPRO-UPS
MIC	AUA01510160001
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit, supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply
Construction	ABS frame with acrylic & PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	N/A – Manual test switch
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Earth Leakage	0.313mA
Inrush Current	3.08A/84uS
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8002178	LED Strip
AUM01570090001 LUBPRO-CKIT-UPS	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.