



# EUBPRO-LI

## CLEVERTRONICS ECONOMY LITHIUM ULTRABLADE PRO EXIT



PRODUCT INFORMATION	
Part Number	EUBPRO-LI
MIC	AUA03510050001
Description	Economy Lithium Ultrablade Pro Blade Exit
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Can be toggled between maintained and non-maintained mode by pressing the test button 5 times within a 4 second period - default setting is maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x LED, 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.8 Watts (Standby), 2.8 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E5 C90=E5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1560200	BATT:EcoLith 3.2V 1.1Ah 210mm lead,noBKT
8002179	PCA:EUBPRO LED Strip Assy (CT10602-x)
AUM03570010001 EUBPRO-CKIT-LI	Ultrablade Pro,Control Only, Eco LI, M/NM F/W

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.