



## LUBPRO-TH-HV-DS-R

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man, Double Sided



### PRODUCT INFORMATION

Part Number	LUBPRO-TH-HV-DS-R
MIC	AUA01860610001
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man, Double Sided
Construction	PC/ABS body with PC diffuser
Mounting	Recessed ceiling, Double-sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Running Man Arrow One Way
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.3 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8002178	LED Strip
AUM01870870001 LUBPRO-CKIT-HV-10	Driver Pack
8003191	HIVE Node (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order