



LUBPRO-DALI-V

CLEVERTRONICS L10 ULTRABLADE PRO WALL MOUNT FLAG STYLE



PRODUCT INFORMATION

Part Number	LUBPRO-DALI-V
MIC	AUA01211230002
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit – Wall mount flag style vertical decal arrangement
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Wall Mount, Single or Double Sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Vertical legend, 1 box solution (all directional inserts included in the box)
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.2 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.25 C90=B1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
AUM01270340003 LUBPRO-CKIT-DALI	Ultrablade Pro, Control Only, Dali Reg, L10 (incl. DALI node)
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order