

CLEVERTRONICS L10 ULTRABLADE PRO



PRODUCT INFORMATION

Part Number	LUBPRO-DALI
MIC	AUA01211000002
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit
Construction	ABS frame with acrylic & PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E6.3 C ₉₀ =E6.3
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
AUM01270340002	Ultrablade Pro, Control Only, Dali Reg, L10
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.