



## LUBPRO-TH-DS-RAOW

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided



### PRODUCT INFORMATION

Part Number	LUBPRO-TH-DS-RAOW
MIC	AUA01360300001
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Running Man Arrow One Way, Double Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8011493	LED Strip
AUM01370640001 LUBPRO-CKIT-10	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.