

CLEVERTRONICS ECONOMY LITHIUM ULTRABLADE PRO SURFACE MOUNT



PRODUCT INFORMATION

| | |
|-----------------------|--|
| Part Number | EUBPRO-SM-LI |
| Description | Economy Lithium Ultrablade Pro Surface Mount blade Exit |
| Construction | PC/ABS body with PC diffuser |
| Mounting | Wall, ceiling single-sided & ceiling double-sided |
| Dimensions L x W x H | 317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base) |
| Weight | 1.0kg |
| Operating Mode | Maintained |
| Testing System | N/A - Manual test switch |
| Battery | Lithium Iron Phosphate, 3.2V 1100mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All pictograph directional inserts included in the box |
| Lamp(s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.8 Watts (Standby), 2.8 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =E6.3 C ₉₀ =E6.3 |
| Viewing Distance | 24m |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|--|
| 1560200 | BATT:EcoLith 3.2V 1.1Ah 210mm lead,noBKT |
| 8002179 | PCA:EUBPRO LED Strip Assy (CT10602-x) |
| 8002983 | PCA: EUBPRO-SM-LI #CT10614-L2 |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

