



LUBPRO-SM-RS-DALI

CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT
SURFACE MOUNTED - ROD SUSPENDED
(DALI)



| PRODUCT INFORMATION | |
|--------------------------|--|
| Part Number | LUBPRO-SM-RS-DALI |
| MIC | AUA01211290002 |
| Description | L10 Optimum Ultrablade Pro Blade Exit, Surface Mounted, Rod suspended, DALI Registered |
| Construction | PC/ABS body with PC Diffuser |
| Mounting | Surface Mount Ceiling - Rod suspended Blade suspended with 5mm diameter; steel rods secured by 2 x "grub-screw" at each end of the rod. Rod suspension system supplies power to the LED lampbar mounted on top of blade. Note: Steel Rods supplied with fitting assembly, 1500mm long. |
| Dimensions L x W x H | Blade Assembly 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 360mm x 47mm x 72mm |
| Cut-Out | 350mm x 48mm |
| Minimum Depth | 80mm |
| Weight | 1.5kg |
| Operating Mode | Maintained |
| Testing System | DALI Registered |
| Battery | Lithium Nanophosphate 3.3V 2.5Ah |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All Directional Inserts Included |
| Lamp(s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.4W (Standby), 3.7W (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=E6.3 C90=E6.3 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

| REPLACEMENT PARTS | |
|-------------------|-------------|
| PART NUMBER | DESCRIPTION |
| 1530030 | Battery |
| 8011493 | LED Strip |
| 8003135 | Driver |
| 8003060 | DALI Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order