



CUBPRO-SM-TH-HV-DS-RAOW

CLEVERTRONICS LP ULTRABLADE PRO SURFACE MOUNT EXIT, DOUBLE SIDED, THEATRE



PRODUCT INFORMATION

Part Number	CUBPRO-SM-TH-HV-DS-RAOW
MIC	AUA02860110001
Description	LP Premium Ultrablade Pro surface mount blade Exit, Theatre
Construction	PC/ABS body with PC diffuser
Mounting	Wall, ceiling single-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, running man with arrow one way, double sided (must specify diffuser combination)
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby) 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	0°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8003503	Driver Pack
8002178	Emergency LED Panel
8003191	Emergency Node – HIVE (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.