



LUBPRO-SM-V

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT FLAG STYLE EXIT



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-V
MIC	AUA01310300001
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit, Surface mount flag style vertical decal arrangement, Enabled with Clevertest Plus
Construction	PC/ABS body with PC diffuser
Mounting	Surface Wall Mount, Single or Double Sided
Dimensions L x W x H	157mm x 8.7mm x 317mm (Blade Assembly) 72mm x 47mm x 360mm (Base)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Vertical legend, 1 box solution (all directional inserts included in the box)
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1 C90=B1
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead, no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8003135	PCA:CUBPRO-SM Driver CT10142-L9 DALI Reg,CTP,HV,ZW

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order