

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT



PRODUCT INFORMATION

Part Number	LUBPRO-SM
MIC	AUA01310230001
Description	L10 Lithium Nanophosphate Ultrablade Pro surface mount blade Exit, Enabled with Clevertest Plus
Construction	PC/ABS body with PC diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E6.3 C ₉₀ =E6.3
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
8002945	PCA:C/LUBPRO-SM #CT10142-L8 CTP

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order