



## LUBPRO-SM-DALI

CLEVERTRONICS L10 ULTRABLADE PRO  
SURFACE MOUNT EXIT



### PRODUCT INFORMATION

Part Number	LUBPRO-SM-DALI
MIC	AUA01211070002
Description	L10 Optimum Ultrablade Pro Surface Mount Blade Exit
Construction	ABS Frame with Acrylic & PC Diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8003135	PCA:CUBPRO-SM Driver CT10142-L9 DALI Reg,CTP,HV,ZW
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.