



CWELED-HV-BLK

CLEVERTRONICS LP WEATHERPROOF EXIT, BLACK
(ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	CWELED-HV-BLK
MIC	AUA02820120002
Description	LP Premium Weatherproof Emergency EXIT, Black
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.7 Watts (Max)
Inrush Current (Max)	TBA
Earth Leakage	TBA
IP Rating	IP66/67
IK Rating	IK10
Operating Temperature	0°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Strip
8002329	Driver
8003190	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.