



## CJWELED-40-DALI

CLEVERTRONICS LP JUMBO WEATHERPROOF UNIVERSAL EXIT



PRODUCT INFORMATION	
Part Number	CJWELED-40-DALI
MIC	AUA02220240002
Description	LP Premium Jumbo Weatherproof Universal Exit
Construction	Polycarbonate
Mounting	Wall mount, Single-sided Ceiling mount, Single & Double-sided
Dimensions L x W x H	570mm x 117mm x 340mm
Weight	5.6kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included
Lamp(s)	12 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.1 Watts (Max)
IP Rating	IP66
IK Rating	IK09
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E4
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	BATT:LP 3.2V 3200mAh 260mm lead, no BRKT
8050640	LED: HWSUB: CT10758-D1
CJELED-40-CKIT-DALI-110	DRIVER: Jumbo LED Exit, Control Kit, LP, DALI, 110mA (incl. DALI node)
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.