



LWELED-A-DALI

CLEVERTRONICS L10 WEATHERPROOF EXIT WITH ACRYLIC COVER



PRODUCT INFORMATION

Part Number	LWELED-A-DALI
MIC	AUA01220110002
Description	L10 Lithium Nanophosphate weatherproof Emergency EXIT with acrylic cover
Construction	Acrylic clear cover, Glass reinforced nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4KG
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4 Watts (Max)
Inrush Current (Max)	51A/22us
Earth Leakage	0.333mA
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
Viewing Distance	24m
AS2293 Classification	C0=D6.3, C90=D5
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002358	Driver
8002710	LED Strip
8003060	Emergency Node - DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.