

CLEVERTRONICS L10 WEATHERPROOF EXIT



PRODUCT INFORMATION

Part Number	LWELED-DALI
MIC	AUA01220120102
Description	L10 Lithium Nanophosphate weatherproof Emergency EXIT
Construction	Polycarbonate clear cover, Glass reinforced nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E2 C ₉₀ =E2
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
8002320	PCA: LCFLED CT10164-L6 6C70 DALI-REG HIVE AU
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order