



LWELED-TH-R

CLEVERTRONICS L10 WEATHERPROOF EXIT, THEATRE



PRODUCT INFORMATION

Part Number	LWELED-TH-R
MIC	AUA01360190002
Description	L10 Optimum Weatherproof Exit, Theatre
Construction	Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base
Mounting	Surface Mounted, Single-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man
Lamp(s)	6 x LED 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.5W (Standby), 3.7W (Max)
Inrush Current (Max)	12.517A, 82µs
Earth Leakage	0.333mA
IP Rating	IP66/67
Operating Temperature	0°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8002348	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.