



LWELED-DALI-WM

CLEVERTRONICS L10 WEATHERPROOF EXIT WALL MOUNT
ONE BOX SOLUTION (DALI)



PRODUCT INFORMATION

| | |
|--------------------------|---|
| Part Number | LWELED-DALI-WM |
| MIC | AUA01220290002 |
| Description | L10 Optimum Wall Mounted Weatherproof Emergency EXIT |
| Construction | Polycarbonate Clear Cover, Polycarbonate Base |
| Mounting | Wall mount, Single-sided |
| Dimensions L x W x H | 380mm x 190mm x 130mm |
| Weight | 2.7kg |
| Operating Mode | Maintained |
| Testing System | DALI Registered |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x High Intensity LED, surface mounted onto a replaceable Lamp Bar LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=55Y/00M) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8 Watts (Standby), 3.8 Watts (Max) |
| IP Rating | IP66/IP67 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C0=E1.6 C90=E1.6 |
| Impact Rating | IK08 (side surface) IK09 (front surface) |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|---------------------------------------|---|
| 1530010 | BATTERY :L10 3.3V 2.5AH 200mm lead, Brkt |
| 8002120 | LED: PCA:Duris P5 6 LED Strip.L10,#CT10166-D1 |
| AUM01870110001 LWELED-CKIT-DALI-50 | DRIVER: WP LED Exit, Control Kit, Dali Reg, L10, 50mA (incl. DALI node) |
| 8003060 | PCA: New DALI #CT10629-Ax |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order