



LWELED-WM-IPREM

CLEVERTRONICS L10 WEATHERPROOF EXIT WALL MOUNT
WITH REMOTE CONTROL GEAR



PRODUCT INFORMATION

Part Number	LWELED-WM-IPREM
MIC	AUA01320110001
Description	L10 Optimum Wall Mounted Weatherproof Emergency EXIT with IP66/67 remote control gear. Test button and charge indicator LED located in remote control gear enclosure under the clear lid. Enabled with Clevertest Plus.
Construction	Polycarbonate Clear Cover, Polycarbonate Base
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 130mm x 190mm (Main Enclosure) 380mm x 130mm x 190mm (Control Pack)
Weight	2.7kg (Main Enclosure)
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x High Intensity LED, surface mounted onto a replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.8 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	-40°C to 40°C (Main Enclosure) 0°C to 40°C (Remote Control Pack)
AS2293 Classification	C0=E1.6 C90=C1.6
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY: L10 3.3V 2.5AH 200mm lead, Brkt
AUM01370350001 LWELED-CKIT-50	DRIVER: WP LED Exit, Control Kit, L10, OWC, CTP, 50mA
8002120	LED: PCA:DLED Cleverfit LightStrip,CT10152-D4

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order



LWELED-WM-IPREM

CLEVERTRONICS L10 WEATHERPROOF EXIT WALL MOUNT
WITH REMOTE CONTROL GEAR

Inter-connecting cable type and distances

In accordance with AS2293, the maximum distance the control gear and battery can be located from the lamp source is 2m before there is a requirement need to run in fire protected cable. Below is a list indicating the maximum distance and cable size required to mount the Weatherproof Exit lamp source 10, 20, 40 & 80m away from the control pack and batteries. Please note that this cable would need to be suitably fire rated. Clevertronics will supply the pack and heads with a short lead and terminal block (contained within each enclosure) for the contractor to supply and wire the appropriate 2-way "extension" cable.

The cable sizes for 10M, 20M, 40M, 80M are as follows:

10M: 1.5 mm²
20M: 1.5 mm²
40M: 2.5 mm²
80M: 2.5 mm²