



LWELED-HV-WM

CLEVERTRONICS L10 WEATHERPROOF EXIT WALL MOUNT
ONE BOX SOLUTION (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	LWELED-HV-WM
MIC	AUA01820200001
Description	L10 Optimum Wall Mounted Weatherproof Emergency EXIT
Construction	Polycarbonate Clear Cover, Polycarbonate Base
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 190mm x 130mm
Weight	2.7kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x High Intensity LED, surface mounted onto a replaceable Lamp Bar LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=55Y/00M)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.8 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=E1.6 C90=E1.6
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY: L10 3.3V 2.5AH 200mm lead, Brkt
8002120	LED: PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
AUM01870300001 LWELED-CKIT-HV-50	DRIVER: WP LED Exit, Control Kit, HV, L10, 50mA (incl. Hive node)
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order