



LCWELED-HV-RR

CLEVERTRONICS L10 CLASSIC WEATHERPROOF EXIT
(ZONWORKS XT HIVE)



PRODUCT INFORMATION	
Part Number	LCWELED-HV-RR
MIC	AUA01820430001
Description	L10 Lithium Nanophosphate Classic Weatherproof Emergency EXIT
Construction	Polycarbonate white opal cover, black glass reinforced nylon PA66 base
Mounting	Wall, Ceiling single-Sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man, Right Arrow (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 5.1 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D8 C90=D6.3
Impact Rating	IK10
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530010	Battery
8002430	Emergency Panel
AUM01870310001 LCWELEDM-CKIT-HV-83	Emergency Driver Pack
8003191	Emergency Node – HIVE (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.