



# LJWELED-WM-40-HV-IPREM-RL

Jumbo 40m IP66/67 Weatherproof Exit, Wall Mount,  
L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow Left,  
Single Sided, Weatherproof Remote Control Gear



PRODUCT INFORMATION	
Part Number	LJWELED-WM-40-HV-IPREM-RL
MIC	AUA01820540001
Description	Jumbo 40m IP66/67 Weatherproof Exit, Wall Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow Left, Single Sided, Weatherproof Remote Control Gear
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount
Dimensions L x W x H	EXIT Sign – 560mm x 130mm x 280mm Remote Control Gear – 380mm x 130mm x 190mm
Weight	5,5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running Man with Left Arrow (Must specify diffuser combination)
Lamp(s)	4 x 5 high intensity, surface mounted onto a replaceable lamp bar – 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	40°C to -40°C - Main enclosure with LED lamp bar 0°C to 40°C - Remote enclosure containing control pack and battery
AS2293 Classification	C <sub>0</sub> =E1.6 C <sub>90</sub> =E1.25
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530010	Battery
8002122	LED Strip
AUM01870050001 LJWELED-40-CKIT-HV	Driver Pack
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order