



LWELED

CLEVERTRONICS L10 WEATHERPROOF EXIT



PRODUCT INFORMATION	
Part Number	LWELED
MIC	AUA01320020002
Description	L10 Optimum Weatherproof Emergency EXIT, Enabled with Clevertest Plus
Construction	Polycarbonate clear Cover, Glass reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D6.3 C90=D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530190	Battery
8002710	LED Panel
8002349	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.