



LWELED-WM-UPS

CLEVERTRONICS WEATHERPROOF EXIT WALL MOUNT
UPS



PRODUCT INFORMATION

Part Number	LWELED-WM-UPS
MIC	AUA01520040001
Description	Wall mounted IP66/67 Weatherproof Exit. Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others)
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 190mm x 130mm
Weight	2.7kg
Operating Mode	Maintained with no integral battery backup (UPS)
Testing System	N/A - Manual test switch
Diffuser	All directional inserts included
Lamp(s)	6 x High intensity LED, surface mounted onto a replaceable lamp bar – 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts
IP Rating	IP66/IP67
Impact Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=E1.6 C90=E1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
AUM01570050001	WP LED Exit, Control Kit, OWC, 50mA, UPS
LWELED-CKIT-50-UPS	
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D4

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order